

OS-203DT



OS-203DT comes complete with ArgoBar, the powerful label design software that allows you to design barcode labels within minutes. In addition, it supports both PPLA and PPLB programming languages for compatibility with other printers.

Designed with the most recent advanced technology, this printer features a built-in tear-bar that is easily reconfigured. You buy only the features your current application requires, with the assurance that the printer can also accommodate your future e business needs.

Specifications	
Printing method	Direct Thermal
Printing resolution	203 dpi (8 dots/mm)
Printing Speed	2 ~ 3.5 ips (51 ~ 88.9 mm/s)
Printing Length	Max 10" (254 mm)
Printing Width	Max 2.83" (72 mm)
Memory	512KB DRAM, 512KB Flash ROM
CPU Type	16 bit RISC, microprocessor
Media Sensor	Reflective
Display	LED indicator x 2
Operation interface	Button x 1
Communication interface	Centronics parallel RS-232 Min Din 6P
Fonts	Int'l character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23"H (1.25mm ~ 6.0mm) All fonts are expandable up to 24 x 24 4 direction 0 ~270 rotation Soft fonts are downloadable
Power Source	21VAC 50/60 Hz or DC24V (min 2.5A) , external power adapter
Barcodes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A, B, C) Codabar, Interleave 2 of 5, EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A, E 2&5 add on, POSTNET, German POST, Matrix 25, Maxicode, PDF-417,Data Matrix
Agency listing	CE, UL, CUL, FCC class A, CCC
Graphics	PPLA: PCX, BMP, IMG, HEX, GDI PPLB: PCX, Binary raster, GDI

Software	Argox PPLA/PPLB Language Windows Driver (Win98/2000/NT/XP) Label editing software - ArgoBar Print Utility
Media	Roll-feed, die-cut, continuous, fan-fold, tags, ticket in thermal paper or plain paper Max width 3.13" (79mm) Min width 1.0" (25.4mm) Thickness 0.0025" ~ 0.01" (0.0635mm ~ 0.254mm) Max roll capacity 4.3" (109mm) OD Core size 1" (25mm) ID
Dimensions	W134 x H163 x L228 mm, 2.6lbs (1.2kgs)
Mechanism request	Fan fold paper back cover, face-out ribbon run way, face-out media run way, un-adjustable TPH carrier
Operation environment	40□ ~ 100□ (4□ ~ 38□) ; 10 ~ 90% non-condensing
Optional items	Cutter, Dispenser kit, Real time clock card, ArgoNet print server, External USB connector, ArgoKee, 2MB Asian Font card (Traditional Chinese, Simplified Chinese, Korean and Japanese)

SMA SOLUTIONS



01/380734 - 01/388116

70/200124

info@smasolution.com

www.smasolution.com